

2.0mm Mini Jumper (Two Circuit Shunt Connector)

■ HOUSING PART NO: 8022

Features & Benefits





- Cost effective alternative to DIP switches
- Dual beam type contacts
- All side and end stackable
- Flexible and easy applied - No soldering
- Mate with 2.0mm Pin Headers

Specifications

- Current Rating: 1A
- Insulation Resistance: 5000m Ω Min.
- Dielectric Withstanding: 600V AC,DC
- Contact Resistance: 20m Ω Max.
- Operating Temperature: -40°C to +105°C

Materials(UL 94V-0)

- Contact Material: Phosphor Bronze
- Contact Plating: Gold/Tin over Nickel
- Insulation Material: Glass Filled Polyester



HO TIEN PRECISION INDUSTRY CO., LTD.
合田精密工業股份有限公司

RECORD OF REVISION / 修定內容	REV.BY / 修定者	REV. DATE / 修定日期	PART NO. / 型號	8022	APPROVED BY / 核准	
			METERIAL / 材質		CHECKED BY / 審查	
			TREATMENT / 表面處理		DRAWN / 製圖	
			CUSTOMER / 客戶名稱		DATE / 製圖日期	
			UNIT / 單位	mm	SCALE / 比例	1/2
					DRAWING TYPE / 圖面種類	