2.0mm Mini Jumper (Two Circuit Shunt Connector)

HOUSING PART NO: 8024

Features & Benefits

- Cost effective alternative to DIP switches
- Dual beam type contacts
- All side and end stackable
- Flexible and easy applied No soldering
- Mate with 2.0mm Pin Headers

Specifications

• Current Rating: 1A

• Insulation Resistance: $5000 \text{m} \Omega$ Min.

• Dielectric Withstanding: 600V AC,DC

• Contact Resistance: 20mΩ Max.


• Operating Temperature: -40°C to +105°C

Materials(UL 94V-0)


• Contact Material: Phosphor Bronze


Contact Plating: Gold/Tin over Nickel

• Insulation Material: Glass Filled Polyester









HO TIEN PRECISION INDUSTRY CO., LTD. 合田精密工業股份有限公司

RECORD OF REVISION / 修定內容	REV.BY / 修定者	REV. DATE / 修定日期	PART NO. / 型號		8024		APPROVED BY / 核淮	
			METERIAL	./ 材質			CHECKED BY / 審查	
			TREATMENT .	/表面處理			DRAWN/製圖	
			CUSTOMER / 客戶名稱				DATE/製圖日期	
			UNIT / 單位	mm	SCALE / 比例	1/2.5	DRAWING TYPE / 圖面種類	